

July 17, 2019

TO U.S. DISTRIBUTORS OF THE ARMSTRONG COMMERCIAL FLOORING PRODUCTS LINE

Subject: Adhesive Portfolio Update: New Options for LVT Installations

In June, we introduced S-1000 and S-980 designated for use with LVT in high RH% concrete slab conditions, for select accounts. Now, these two adhesives are available to all customers. Product information is available on the [commercial website](#). Our [LVT installation guide](#), and the [Adhesive Digital Brochure](#) have been updated as well.

We are also happy to announce our S-310 Roll Strong™ adhesive is available in a 1 gallon size. Please find attached product specifications for all three products. Price lists have been updated.

	S-1000 Adhesive	S-980 Adhesive	S-310 Roll Strong™ 1 Gallon
SKU Number	FPS1000208	FP00980418	FPS00310108
Container Size	2 gal	4 gal	1 gal
RH	≤ 100%	≤ 98%	≤ 90%
PH	5-14	5-12	5-11
MVER	14	12	NA
VOC, SCAQMD 1168	0.1 g/L	14 g/L	0 g/L
Trowel	1/32" deep x 1/16" wide x 1/16" apart, U-Notch	1/16" deep x 1/16" wide x 1/16" apart, Square Notch	Roll on with 3/8" Nap Roller

As we add new, high-performing adhesives to our offering, we continue to test and evaluate our entire adhesive portfolio to ensure we are making the right recommendations for successful installations. As a result, we have changed the recommended trowel for Natural Creations® with Diamond 10® Technology installations using [S-288 Flooring Adhesive](#); see chart below. Previously the recommended trowel for S-288 was the same for all installations (1/32" x 1/16" x 5/64").

S-288 Flooring Adhesive	Recommended Trowel	Spread Rate
Natural Creations with Diamond 10 Technology	1/32" deep; 1/16" wide; 1/32" apart, U-Notch	220-260 sq. ft. / gal
All Other Products (sheet, rigid core, Alterna®)	1/32" deep; 1/16" wide; 5/64" apart. Fine Notch	250-300 sq. ft. / gal

Thank you for your continued support of our Installation, Maintenance and Accessories business. If you have any questions about these adhesive updates, please contact me.

Sincerely,



Brian Saker
Director, Product Management